

<b>NAVY SHIPS PARTS CONTROL CENTER SPECIAL PACKAGING INSTRUCTION (SPI)</b>			<b>CODE IDENT</b> 03950	<b>SPI NO.</b> 10121
<b>NOMENCLATURE</b> DESICCANT		<b>NATIONAL STOCK NUMBER</b> 1H 3655-00-689-6438 CP		<b>DATE</b> 6 APR 93
				<b>REV</b> B
<b>QUP</b>	<b>MAX. UNIT PACKAGE WT.</b>	<b>MAX. UNIT PACKAGE CUBE</b>	<b>MAX. UNIT PACKAGE DIMS.</b>	<b>Drawn By</b> <i>[Signature]</i> <b>Approved</b> <i>[Signature]</i>
1	1.25 LBS	0.021 CU FT	4" X 3" X 3"	<b>Sheet 1 of 1</b>

Preparation: Desiccant is manufactured in a sterile environment, assembled in a clean room and sealed in a clean canister. Cleanliness shall be certified by the manufacturer and shall not be compromised during the packaging process. The canisters shall be sealed with sealing wax.

Labeling: A warning label shall be placed on the outside of each canister. The label shall be fabricated from green paper, similar to color #14187 in FED-STD-595 (latest revision). Lettering shall be easily read and black in color. The label shall read:

**WARNING!!!**  
THIS MATERIAL WAS MANUFACTURED AND ASSEMBLED  
IN A CLEAN ENVIRONMENT  
DO NOT OPEN UNTIL READY FOR USE.

Packing: Packing for shipment shall be accomplished in accordance with the requirements of MIL-STD-2073 Level A for overseas shipments, Level C for domestic shipments, unless otherwise specified. Shipping containers shall be selected from Table I of MIL-STD-2073.

Marking: Each canister and exterior package shall be marked with MIL-STD-129 markings.