

| | | | | | | |
|---|--------------------------------|------------------------------|--|------------|--------------------------------|----------|
| NAVAL INVENTORY CONTROL POINT | | | | CODE IDENT | SPI NUMBER | |
| SPECIAL PACKAGING INSTRUCTION (SPI) | | | | 03950 | 10142 | |
| NOMENCLATURE TILES, FLAT RUBBER, TYPE 14 W/PSA | | | NATIONAL STOCK NUMBER 3H 7320-01-437-9541 | | DATE 13 MAY 1997 | REV A |
| QUP | MAXIMUM UNIT PACKAGE WEIGHT | MAXIMUM UNIT PACKAGE CUBE | MAXIMUM UNIT PACKAGE DIMENTIONS | | DRAWN BY: KWS APPROVED: GWW | |
| 040 | 195.0 LBS | 5.334 CU FT | 32" X 32" X 9" | | SHEET | 1 OF 1 |

PRESERVATION, PACKAGING AND PACKING REQUIREMENTS PER MIL-STD-2073-1C:

| H | M | QUP | ICQ | PRES METH | C D | PRES MATL | WRAP MATL | CUSH DUNN | C T | UNIT CTNR | L P | INTM CTNR | U C L | SPEC MKG | PACK- ING | UNIT PACK WEIGHT | UNIT PACK CUBE | O P I |
|---|---|-----|-----|--------------|--------|--------------|--------------|--------------|--------|--------------|--------|--------------|-------------|-------------|--------------|------------------------|----------------------|-------------|
| N | | 040 | 000 | 10 | 1 | 00 | ZZ | 00 | 0 | ZZ | A | 00 | A | 32 | FFF | 195.0 | 5.334 | A |

1. The item shall be packaged in accordance with the above packaging requirements code and the following:

a. Separate each tile with brown kraft paper.

b. Tiles with Pressure Sensitive Adhesive have a shelf-life and shall be marked IAW MIL-STD-129 requirements.

c. Construct each crate with the outside frame made from 2" X 4" lumber and a top and bottom made from 3/8" plywood each reinforced with 1" X 4" lumber. The runners on the base will be 2" X 4" lumber. See example below: