

NAVAL INVENTORY CONTROL POINT			CODE IDENT	SPI NUMBER
SPECIAL PACKAGING INSTRUCTION (SPI)			03950	10144
NOMENCLATURE TYPE 15 REFLECTIVE TARPS		NATIONAL STOCK NUMBER Various (see below)		DATE 15 MAY 1997
QUP	MAXIMUM UNIT PACKAGE WEIGHT	MAXIMUM UNIT PACKAGE CUBE	MAXIMUM UNIT PACKAGE DIMENTIONS	DRAWN BY: KWS APPROVED: GWW
001	VARIOUS	VARIOUS	VARIOUS	SHEET 1 OF 2

NSNs: 3H 5840-01-437-9570 155" X 94" X 5/8" 55 LBS
3H 5840-01-437-9549 165" X 94" X 5/8" 65 LBS

PRESERVATION, PACKAGING and PACKING REQUIREMENTS DATA PER MIL-STD-2073-1C:

H	M	QUP	ICQ	PRES METH	C	PRES MATL	WRAP MATL	CUSH DUNN	C	UNIT CTNR	L	INTM CTNR	U	SPEC MKG	PACK- ING	UNIT PACK WEIGHT	UNIT PACK CUBE	O P I
N		001	004	31	1	00	CA	00	0	ED	A	DP	B	51	EFF			A

1. The item shall be packaged in accordance with the above packaging requirements code and the following:

a. Fold each tarp to a maximum size of 30" x 30" x 6" and wrap each in brown kraft paper. Enclose each item in a MIL-B-121 bag Type 1, Grade A, Class 1. Insert into a fiberboard box per ASTM 5118D/5118M, Type CF, Weather Resistant. Tape each box securely with PVC tape and affix a label to the box identifying the product nomenclature, part number, serial number and date of manufacture.

b. Stack a maximum of four packages with sequential serial numbers into a TRI-WALL corrugated fiberboard box, not to exceed 40" x 40" x 25". Fill any voids with cellulosic wadding.

c. Enclose the packing label in an envelope on top, fold the box flaps over, then staple and tape closed. Affix the shipping label, denoting the serial numbers of each panel, to the outside of the box.

d. Each TRI-WALL shall be placed on and banded to a pallet for ease of handling (see Example 1 on page 2).

NAVY SHIPS PARTS CONTROL CENTER		CODE IDENT		SPI NUMBER	
SPECIAL PACKAGING INSTRUCTION (SPI)		03950		10144	
NOMENCLATURE TYPE 15 REFLECTIVE TARPS		NATIONAL STOCK NUMBER Various (see page 1)		DATE 15 May 1997	REV A
<p>Example 1</p>				SHEET 2 OF 2	